

Hinges & pivots	A31
Pulls & plates	B
Flush bolts & coordinators	C
Latches, catches & bolts	D
Stops	E
Exterior hardware	F
Miscellaneous hardware	G



112HD Full mortise - narrow frame and door leaf

- For 1 3/4" doors
- Spread bearing design
- Non Handed for custom cut lengths
- Flush mounted, no inset
- 48" Maximum door width
- Beveled or square edge doors
- For doors weighing up to 450 pounds without reinforcing, 600 pounds with reinforcing

Certifications

- Meets ANSI 156.26 for 150lbs
- UL10C certified

Standard lengths

- 83", 85", 95", 120"

Standard Mounting Hardware

- 12-24 x 3/4" Steel self drilling / self tapping phillips head screw

Finishes

- Clear Anodized (US28), Dark Bronze Anodized (313AN)

Custom anodizing and painting are available, consult factory.

Options:

- EPTElectric power transfer

Optional mounting hardware:

- SECHM.....Security screws - hollow metal door and frame
- SECWDHM.....Security screws - 1/2 wood, 1/2 hollow metal
- SECWDWDSecurity screws - wood door and frame
- TFThread forming screws
- TEKWD1/2 self drill, self tap 1/2 wood
- WD.....Wood door and frame

For single door applications:

For pairs of doors see chart and general information

